

Proxmox container 'nextcloud.test'

Status

- läuft, beta

Container setup

- image: debian10 with users
- 1. Netzwerkkarte
 - eth0
 - 10.2.0.20/24 DG: 10.2.0.254; fd00:10:2:0::20/64 DGfd00:10:2:0::0
 - bridge: vmbr0
- 2. Netzwerkkarte:
 - eth1,
 - 10.3.0.20/24 DG: 10.3.0.254; fd00:10:3:0::20/64 DGfd00:10:3:0::0
 - bridge: vmbr1

Ansible setup

- verbindet man sich als unprivilegierter user und möchte ein Command als ein anderer, unprivilegierter user ausführen (z.B. www-data), benötigt man

```
allow_world_readable_tmpfiles = yes
```

in der ansible.cfg, damit dies nicht als Fehler zum Abbruch führt.

Ansible Script

```
#!/usr/bin/env ansible-playbook
```

```
- name: 'install nextcloud'
  hosts: nextcloud
  become: true
```

```
tasks:
```

```
- name: remove apache2
  apt:
    name: apache2
    state: absent
```

```
- name: install packages
```

```
  apt:
```

```
    pkg:
```

- php7.3
- php7.3-curl
- php7.3-gd
- php7.3-json
- php7.3-xml
- php7.3-mbstring
- php7.3-zip
- php7.3-mysql
- php7.3-bz2
- php7.3-intl
- php7.3-redis
- php7.3-imagick
- php7.3-fpm
- ffmpeg

```
- nginx

- name: check if nextcloud is already installed
  stat:
    path: /var/www/nextcloud
    register: nextcloud_exists

- name: Download nextcloud and unpack
  unarchive:
    src: https://download.nextcloud.com/server/releases/nextcloud-20.0.0.zip
    dest: /var/www
    owner: www-data
    group: www-data
    remote_src: yes
  when: not nextcloud_exists.stat.exists

- name: Remove file packed file
  file:
    path: /var/www/nextcloud-20.0.0.zip
    state: absent

- name: first setup nextcloud
  become_user: www-data
  become: yes
  shell: |
    php occ maintenance:install --database mysql --database-host 10.3.0.100 --database-
name nextcloud --database-port 3306 --database-user nc_user --database-pass 'dbpass' --
admin-user admin --admin-pass 'ampass' --data-dir /var/www/nextcloud/data
  args:
    chdir: /var/www/nextcloud/
    creates: /var/www/nextcloud/config/config.php

- name: add domain to trusted domains
  become_user: www-data
  become: yes
  lineinfile:
    path: /var/www/nextcloud/config/config.php
    insertafter: .*localhost.*
    line: "    1 => 'bytecluster0002.bytespeicher.org'"
    firstmatch: yes

- name: copy nginx config
  copy:
    src: ./conf/nextcloud.conf
    dest: /etc/nginx/sites-available/
    owner: root
    group: root
    mode: '0744'

- name: Create a symbolic link
  file:
    src: /etc/nginx/sites-available/nextcloud.conf
    dest: /etc/nginx/sites-enabled/nextcloud.conf
    owner: root
    group: root
    state: link

- name: load php-fpm
  systemd:
    state: restarted
    name: php7.3-fpm
```

```
- name: Restart nginx
  systemd:
    state: restarted
    daemon_reload: yes
    name: nginx
```

Notizen

- Ansible script lädt momentan das .zip nicht herunter. Fehler unbekannt.
- Sonderzeichen in Passwörtern führen zu Fehlern. Genaue Escape-Sequence noch unbekannt.

Dauerhafter Link zu diesem Dokument:

<https://wiki.technikkultur-erfurt.de/dienste:bytecluster0002:nextcloud?rev=1601930787>

Dokument zuletzt bearbeitet am: **05.10.2020 22:46**

Verein zur Förderung von Technikkultur in Erfurt e.V

<https://wiki.technikkultur-erfurt.de/>

